

FLASH HOOD



Firefighter flash hood




Certification according to EN 13911:2017

Details:

- ⊕ Inherently flame retardant flash hood with Prevent® particulate blocking barrier.
- ⊕ Elasticated front opening, to integrate with multiple face masks.
- ⊕ Panelled head area to give greater wearer comfort and security.
- ⊕ Shoulder bib extends from front opening to fit under tunic providing full all round coverage.
- ⊕ > 99.9% Particulate protection even after 100 washes - IBR JN: 18478A.
- ⊕ Outstanding performance after each and every wash/wear cycle, without degradation.
- ⊕ Seamless front panelling to prevent carcinogenic ingress in *vulnerable areas

*noted results from FAST testing



<u>OUTERSHELL</u>	<u>MEMBRANE BARRIER</u>	<u>WEIGHT / M²</u>	<u>COLOURS</u>
NOMEX® 93% meta-aramid / 5% para-aramid / 2% antistat	100% meta-aramid knit with PTFe barrier (complete barrier fitting)	375	
NOMEX® 93% meta-aramid / 5% para-aramid / 2% antistat	100% meta-aramid knit with PTFe barrier (Single knit crown for enhanced breathability)	375	
PBI® 40% polybenzimidazole / 60% para-aramid	100% meta-aramid knit with PTFe barrier (complete barrier fitting)	295 / 405	
PBI® 40% polybenzimidazole / 60% para-aramid	100% meta-aramid knit with PTFe barrier (Single knit crown for enhanced breathability)	405	